

土工膜焊接机						
功能	热楔焊接机（双侧进膜）				热楔焊接机（同侧进膜）	热风焊接机（双侧进膜）
型号	SWT-NS800	SWT-NS810	SWT-NS-GM1	SWT-NS900	SWT-NS-GM2	SWT-NS700
功率	800W	800W	1300W	1800W	1200W	3000W
重量	5.0KG	5.0KG	9.0KG	13.0KG	7.5KG	7.5KG
搭接宽度	10CM	15CM	12CM	12CM	12CM	16CM
焊接速度	1.0-5.5m/min	1.0-5.5m/min	0.3-5.0m/min	0.9-6.3m/min	0.3-5.0m/min	0.3-2.15m/min
温度	20-480℃ 可调	20-450℃ 可调	20-450℃ 可调	20-450℃ 可调	20-450℃ 可调	20-620℃ 可调
焊缝宽度	12.5MM*2, 空腔12MM	15MM*2, 空腔12MM	15MM*2, 空腔20MM	15MM*2, 空腔15MM	15MM*2, 空腔20MM	15MM*2, 空腔15MM
焊接厚度	0.2-1.5MM	0.2-1.5MM	0.2-2.0MM	1.0-3.0MM	0.2-2.0MM	0.5-2.0MM
挤出式焊枪						
功能	双极加热					
型号	SWT-NS600A	SWT-NS600B	SWT-NS600C	SWT-NS610A	SWT-NS610B	SWT-NS610C
挤出功率	800W			1300W		
热风功率	1600W	3400W	1600W	1600W	3400W	1600W
焊条加热功率	800W					
风温	20-620℃ 可调					
挤出温度	200-380℃ 可调					
挤出量	2.0kg/h			2.5kg/h		
焊条直径	φ3.0-4.0mm			φ3.0-4.0mm, 5.0mm可定制		
重量	6.5KG			7.0KG		
驱动电机	HITACHI 日立			METABO 麦太保		
建议焊接厚度	1-20 mm	8-40mm	1-20mm	1-20mm	8-40mm	1-20mm
功能	单极加热			颗粒式挤出		
型号	SWT-NS600E	SWT-NS600F	SWT-NS610E	SWT-NS620C		
挤出功率	800W	1200W	1300W	1300W		
热风功率	3400W			1600W		
颗粒加热功率				800W		
风温	20-620℃ 可调			20-620℃ 可调		

挤出温度				200-380°C 可调
挤出量	2.0kg/h	2.5kg/h	2.5kg/h	3.5kg/h
焊条直径	φ3.0-4.0mm			塑料颗粒
重量	6.5KG	7.0KG	7.0KG	8.0KG
驱动电机	HITACHI 日立	FEIJI 飞机	METABO 麦太保	METABO 麦太保
建议焊接厚度	1-10mm			5-40mm



### 热风焊接机

功能	PVC/TPO卷材焊接	SBS改性沥青焊接	立面焊接	半自动焊接
型号	SWT-NS-WP1	SWT-NS-WP2	SWT-NS-VET	SWT-NS-TAC
功率	4200W	4200W	4200W	1700W
焊接速度	1.0-10.0m/min	1.0-10.0m/min	1.0-10.0m/min	0.5-5.0m/min
加热温度	20-620°C 可调	20-620°C 可调	20-620°C 可调	20-620°C 可调
焊接压力	200N,可加配重			
焊缝宽度	40mm	80mm	40mm	40mm
焊接高度			80-160mm	
重量	37KG	37KG	40KG	5KG

### 广告布/篷布焊接机











功能	广告布焊接	广告布/篷布焊接	
焊接方式	搭接焊接/折边焊接/穿绳焊接	搭接焊接	贴带焊接
型号	SWT-NS-UMES	SWT-NS-MAT	SWT-NS-MAT2
功率	3000W	4200W	4200W
焊接速度	1.5-11.6m/min	1.0-10.0m/min	1.0-10.0m/min
加热温度	20-620°C 可调	20-620°C 可调	20-620°C 可调
焊缝宽度	20/30/40mm	40	40mm
重量	12.5KG	22KG	24KG

## 挤出式焊枪




功能	双极加热					
型号	SWT-NS600A	SWT-NS600B	SWT-NS600C	SWT-NS610A	SWT-NS610B	SWT-NS610C
图片						
挤出功率	800W			1300W		
热风功率	1600W	3400W	1600W	1600W	3400W	1600W
焊条加热功率	800W					
风温	20-620℃ 可调					
挤出温度	200-380℃ 可调					
挤出量	2.0kg/h			2.5kg/h		
焊条直径	φ3.0-4.0mm			φ3.0-4.0mm, 5.0mm可定制		
重量	6.5KG			7.0KG		
驱动电机	HITACHI 日立			METABO 麦太保		
建议焊接厚度	1-20 mm	8-40mm	1-20mm	1-20mm	8-40mm	1-20mm

价格						
功能	单极加热			功能	颗粒式挤出	
型号	SWT-NS600E	SWT-NS600F	SWT-NS610E	型号	SWT-NS620C	
图片				图片		
挤出功率	800W	1200W	1300W	挤出功率	1300W	
热风功率	3400W			热风功率	1600W	
				颗粒加热功率	800W	
风温	20-620°C 可调			风温	20-620°C 可调	
挤出温度				挤出温度	200-380°C 可调	
挤出量	2.0kg/h	2.5kg/h	2.5kg/h	挤出量	3.5kg/h	
焊条直径	φ3.0-4.0mm			焊条直径	塑料颗粒	
重量	6.5KG	7.0KG	7.0KG	重量	8.0KG	
驱动电机	HITACHI 日立	FEIJI 飞机	METABO 麦太保	驱动电机	METABO 麦太保	
建议焊接厚度	1-10mm			建议焊接厚度	5-40mm	
价格				价格		





## HAND EXTRUSION WELDING GUN SERIES

Features	1. dual heating systems, 2. LCD temperature controller, 3. motor cold protection, 4. 360° rotating welding head or 2 different angle welding head					
Model	SWT-NS600A	SWT-NS600B	SWT-NS600C	SWT-NS610A	SWT-NS610B	SWT-NS610C
Photo						
Extruding Power	800W			1300W		
Hot Air Power	1600W	3400W	1600W	1600W	3400W	1600W
Welding Rod Heater Power	800W					
Air Temperature	20-620°C Adjustable					
Extruding Temperature	200-380°C Adjustable					
Extruding Volume	2.0kg/h			2.5kg/h		
Welding Rod Diameter	φ3.0-4.0mm			φ3.0-4.0mm, 5.0mm can be customized		
Net Weight	6.5KG			7.0KG		
Driving Motor	HITACHI			METABO		
Materials thickness	1-20 mm	8-40mm	1-20mm	1-20mm	8-40mm	1-20mm
EXW Price						
Features	1. 3400w powerful heating system, 2. 360° rotating welding head			Features	1. dual heating systems, 2. LCD temperature controller, 3. motor cold protection, 4. 360° rotating welding head	
Model	SWT-NS600E	SWT-NS600F	SWT-NS610E	Model	SWT-NS620C	
Photo				Photo		
Extruding Power	800W	1200W	1300W	Extruding Power	1300W	
Hot Air Power	3400W			Hot Air Power	1600W	
				Granules Heater Power	800W	
Air Temperature	20-620°C adjustable			Air Temperature	20-620°C	
Extruding Temperature				Extruding Temperature	200-380°C	
Extruding Volume	2.0kg/h	2.5kg/h	2.5kg/h	Extruding Volume	3.5kg/h	
Welding Rod Diameter	φ3.0-4.0mm			Materials	Granules	
Net Weight	6.5KG	7.0KG	7.0KG	Net Weight	8.0KG	
Driving Motor	HITACHI	FEUJI	METABO	Driving Motor	METABO	
Materials thickness	1-10mm			Materials thickness	5-40mm	
EXW Price				EXW Price		








2.Packing Details: Aluminium Box inner & Carton Box outer

Banner/ Tent / Tarpaulin Welder				Hand Hot Air Gun
Application	for banner,canvas and other thin materials	for banner, tent, tarpaulin and other thick materials		for handle welding
Welding Way	overlap/hem /rope welding	overlap welding	tape welding	overlap or welding rod welding
Model	SWT-NS-UME	SWT-NS-MAT1	SWT-NS-MAT2	SWT-NS1600S
EXW Price				
Photo				
Power	3000W	4200W	4200W	1600W
Welding Speed	1.5-11.6m/min	1.0-10.0m/min	1.0-10.0m/min	
Heating Temperature	20-620°C Adjustable	20-620°C Adjustable	20-620°C Adjustable	20-620°C Adjustable
Welding Seam	20/30/40mm	40mm	40mm	20/40mm
Net Weight	12.5KG	22KG	24KG	1.2KG

Ploymer Hot Air Welding Machine

Application	PVC/TPO/CPE/EPDM Welding	SBS Builtmen Welding	Parapet Welding	Semi-automatic Overlap Welding
Model	SWT-NS-WP1	SWT-NS-WP2	SWT-NS-VET	SWT-NS-TAC
EXW Price				
Photo				
功率	4200W	4200W	4200W	1700W
Welding Speed	1.0-10.0m/min	1.0-10.0m/min	1.0-10.0m/min	0.5-5.0m/min
Heating Temperature	20-620°C Adjustable	20-620°C Adjustable	20-620°C Adjustable	20-620°C Adjustable
Welding Pressure	200N, addible	200N,addible	200N,addible	
Welding Seam	40mm	80mm	40mm	40mm
Welding Height			80-160mm	
Net Weight	37KG	37KG	40KG	5KG

## GEOMEMBRANE WELDER

MODEL	SWT-NS700	SWT-NS800	SWT-NS800D	SWT-NSGM1	SWT-NSGM2	SWT-NS900	SWT-NS900D
PHOTO							
INPUT VOLTAGE	220V/110V,50/60Hz	220V/110V,50/60Hz	220V/110V,50/60Hz	220V/110V,50/60Hz	220V/110V,50/60Hz	220V/110V,50/60Hz	220V/110V,50/60Hz
POWER	3000W	800W	800W	1200W	1200W	1800W	1800W
WEIGHT	7.5KG	5.0KG	5.0KG	7.5KG	7.5KG	13.0KG	13.0KG
OVERLAP WIDTH	16CM	10CM	10CM	12CM	12CM	12CM	12CM
WELDING SPEED	0.2-6m/min	0.5-5.0m/min	0.5-5.0m/min	0.5-8.0m/min	0.5-8.0m/min	0.5-5.0m/min	0.5-5.0m/min
TEMPERATURE	20-620°C ADJUSTABLE	20-450°C ADJUSTABLE	20-450°C ADJUSTABLE	20-450°C ADJUSTABLE	20-450°C ADJUSTABLE	20-450°C ADJUSTABLE	20-450°C ADJUSTABLE
SAEM WIDTH	15MM*2, INTERIOR CAVITY 15MM	12.5MM*2, INTERIOR CAVITY 12MM	15MM*2, INTERIOR CAVITY 12MM	15MM*2, INTERIOR CAVITY 20MM	15MM*2, INTERIOR CAVITY 20MM	15MM*2, INTERIOR CAVITY 15MM	15MM*2, INTERIOR CAVITY 15MM
WELDING THICKNESS	0.5-3.0MM	0.2-1.5MM	0.2-1.5MM	0.2-2.0MM	0.2-2.0MM	1.0-3.0MM	1.0-3.0MM